G-Net TP Range Products Polyethylene Tri-planar Geonet

Technical Data Sheet

GEO-LINK TP Geonet Dec.11th, 2011

OPAH My 2

TP Geonet is tri-planar structure, polyethylene rope as material made by heat treatment. Its' mainly function is to prevent soil erosion and reinforcement for slope soil. According to customer requirements, could composite geotextile or other material.

Physical Properties

<u> </u>			
Properties	Units	Standard	
Structure			3 ribs
Polymer			HDPE
U.V. Stablizer			Carbon black
Foaming Agent			NO

Hydraulic Transmissivity[ASTM D4716]

F	Properties	Standard	Units	G750	G1000	G1300
	Thickness	[ASTM D5199]	mm	5.0	6.0	7.0
Hydraulic Flow Rate						
i=1	σv = 20 KPa	[ASTM D4716]	I/m/s	1.32	1.44	i=1
i=1	σv = 100 KPa	[ASTM D4716]	I/m/s	1.08	1.23	i=1
i=1	σv = 200 KPa	[ASTM D4716]	I/m/s	0.96	1.08	i=1
i=1	σv = 500 KPa	[ASTM D4716]	I/m/s	0.87	0.92	i=1
Ten	sile Strength	[ASTM D4595]	KN/m	19.0	23.0	26.0
E	Elongation	[ASTM D4595]	%	40	50	50

Geotextile Characteristics	Standard	Units	G750	G1000	G1300
Mass per Unit Weight		g/m2	110-130	110-130	110-130
Opening Size	[ASTM D4751]	mm	0.07	0.07	0.07

_	Product Code Drainage	Pressure (KPa)	Residual Thickness at	Residual Thickness at	
			10000 hours(1 year)(%)	30years(extrapolated)(%)	
	G750	100	87.50	86.20	
	G750	200	81.60	81.30	
	G750	500	70.70	68.10	
	G1300	200	90.00	89.50	
	G1300	500	82.00	78.50	

Above values are on an average basis, the data was obtained from in-house test laboratory, National test institutes and international test institutes. GEO-LINK keeps the right of data changes and the final explanation right. Liability Exclusion: This publication should not be construed as engineering advice. While information contained here is accurate to the best of our knowledge, GEO-LINK does not warrant its accuracy or completeness. The only warranty made by GEO-LINK for its products is set forth in our Product Test Report accompanies our shipment of the products, or such other written warranty as may be agreed by GEO-LINK and customer. GEO-LINK specifically disclaims all other warranties, express or implied, including without agreed by GEO-LINK and customer. GEO-LINK specifically disclaims all other warranties, express or implied, including without limitation, warranties of merchantability or fitness for a particular purpose, or rising from provision of samples, a course of dealing or usage of trade.

Dalian Geo-Link Geosynthetics Co.,Ltd.

Add: No.8888-1 Southeast Industrial Zone, Youjia, Ganjingzi District, Dalian, China P.C.: 116039 Tel: +86-(0)411 6600 7883 Fax: +86-(0)411 6600 7882 WebSite: www.geo-textile.com E-Mail: info@geo-textile.com







