## G-Grid HDPE Range Products HDPE Uniaxial Geogrid

## **Technical Data Sheet**

GEO-LINK HDPE Uniaxial Geogrid Dec. 19th, 2009

G-Grid HDPE is a generic name for flexible synthetic mats or meshes used to stabilize large areas of soil. They are made of high strength plastics woven polyester yarns or glass fabric yarns and are typically package din rolls. Geogrids vary in strength and are rated by Long-Term Allowable Design Strength.

| Items                             | Unit  | Specification |         |         |          |          |          |
|-----------------------------------|-------|---------------|---------|---------|----------|----------|----------|
|                                   |       | HDPE 50       | HDPE 65 | HDPE 80 | HDPE 100 | HDPE 120 | HDPE 160 |
| Carbon Black Content              | ≥%    | 2             | 2       | 2       | 2        | 2        | 2        |
| Tensile Strength                  | ≥KN/m | 50            | 65      | 80      | 100      | 120      | 160      |
| Tensile Strength at 2% Elongation | ≥KN/m | 13            | 18      | 23      | 29       | 35       | 47       |
| Tensile Strength at 5% Elongation | ≥KN/m | 25            | 35      | 44      | 55       | 65       | 85       |
| Yield Elongation Ratio            | ≤%    | 12            | 12      | 12      | 12       | 12       | 12       |
| Maximum Creep Strength            | KN/m  | 24.1          | 25.5    | 31      | 39       | 46       | 60       |
| Approx Load Q'ty per 40'HQ        | $m^2$ | 40000         | 32950   | 31900   | 30000    | 25080    | 18750    |

Above values are on an average basis, the data was obtained from in-house test laboratory, National test institutes and international test institutes. GEO-LINK keeps the right of data changes and the final explanation right. Liability Exclusion: This publication should not be construed as engineering advice. While information contained here is accurate to the best of our knowledge, GEO-LINK does not warrant its accuracy or completeness. The only warranty made by GEO-LINK for its products is set forth in our Product Test Report accompanies our shipment of the products, or such other written warranty as may be agreed by GEO-LINK and customer. GEO-LINK specifically disclaims all other warranties, express or implied, including without agreed by GEO-LINK and customer. GEO-LINK specifically disclaims all other warranties, express or implied, including without limitation, warranties of merchantability or fitness for a particular purpose, or rising from provision of samples, a course of dealing or usage of trade.

Dalian Geo-Link Geosynthetics Co.,Ltd.

Add: No.8888-1 Southeast Industrial Zone, Youjia, Ganjingzi District, Dalian, China P.C.: 116039

Tel: +86-(0)411 6600 7885 Fax: +86-(0)411 6600 7882 WebSite: www.geo-textile.com E-Mail: info@geo-textile.com

















